

H.265

High Efficiency Video Coding



Caratteristiche

- * 4.0Megapixel, Clear image
- * H.265 / H.264 video Compressione
- * Supporta 2D/3D noise reduction,digital wide dynamic
- * Super low rate, high definition qualità immagine
- * Multiple network monitoring: Web , CMS, App
- * Mobile app:Sri Lite Web: www.sricam.it/sri
- * Professional anti-lightning
- * Supporta cloud technology,allarme Push
- * Supporta Onvif
- * Built in PoE
- * Audio, Alarm, USB(3G/WiFi) functions
- * 2.8 Fissa MP HD lente
- * Max. IR LEDs length 35meters
- * IP66 Waterproof
- DC12V

Modello	OBA-Lite 35P					
Sensore/Chipset	1/3"OV4689+HI3516D					
Risoluzione	4Mega-Pixel 720P					
Pixels effettivi	2592(H)×1520(V)					
Video Frame Rate	4MP@15fps/3MP@25fps					
Mini. Illuminazione	B/W 0.001Lux@F1.2					
	Color 0.01Lux @F1.2					
Compressione Video	H.265/H.264, support dual stream, AVI;0.1M~10Mbps variable;1-30f/s variable					
Wide dynamic	Support digital					
Compressione Video	H.265/H.264 video encoding, supports dual stream, AVI format; stream 0.1M ~ 8Mbps; support frame rate 1 to 30 frames/S					
Main stream	4MP 2592×1520@15fps;3MP 2048*1536@25fps					
Sub Stream	1280*720,704*576@25fps					
Caratteristiche Camera						
Max. IR LEDs Length	IR led: 5*36pcs IR leds,night visione:35metri					
Day/Night	Color / Black & White / Auto; IR Cut Filter With Auto Switch					
Noise Reduction	3D	3D	3D	3D	3D	3D
Lente						
Focale	2,8mm					
tipo	F1.4	Angolo di visuale	80°			
Video & Audio						
Video	H.265/H.264 Compressione					
Bit Rate	H.265: 25K ~ 6Mbps					
Interfaccia Audio	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support microphone;					
Compressione Audio	G.711,support bidirectional talk,audio&video synchronization;					
Network						
Ethernet	RJ-45 (10/100Base-T),Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP...etc					
Lightning Protection	Power,Net,POE Full Lightning protection,Standard GB/T17626.5 & IEC61000-4-5					
Software:	Supporta WEB configuration, supporta OSD, supporta real-time video transmission, Supporta motion detection linkage end storage; supporta JPEG capture; Screen Pop-up Linkage;Supporta client software remote monitoring(CMS),P2P Treamite APP Sri Lite e web Sricam.it/sri					
Onvif	ONVIF,CGI					
Remote View	Computer: IE6.0 e successivi,Max 10 utenti					
Smart Phone	Mobile Phone: iPhone, iPad, Android, Android pad					
Altro						
PoE	Supporta IEEE 802.3af					
P2P/Cloud	Si					
USB	1*USB,supporta WiFi/3G					
WiFi	Si					
Singal interface	One photo resistance interface,one IR-CUT interface ,support					
Generale						
Power	DC12V±10%; Max 3W,12V 2A input					
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)					
Vandal Resistance	IP66 Waterproof					
Dimensioni(W×D×H)	157(L)*65(W)*65(H)mm					
Peso	450g					