© OBA Security è un marchio registrato da OBA srls
VIA LEPANTO, 132 - 80045 POMPEI (NA) – ITALY P.IVA e C:F.: 07750391216
I prodotti possono subire modifiche senza preavviso.

Network Onvif HD IP camera-IP66 Waterproof Outdoor/Indoor IR visione notturna 20 metri





Caratteristiche

- 1.0Megapixel Clear image
- H.264 & MJPEG
- Supporta 2D/3D noise reduction,digital wide dynamic;
- Day/Night (ICR),2DNR, AWB, AGC, BLC,motion detection.
- Multiple network monitoring: Web, CMS
- Mobile app:Oba Lite Web: www.obasecurity.com
- Professional anti-lightning, standard GB/T17626.5 &IEC61000-4-5
- Support Onvif
- Varifocale 2,8-12mm MP HD lente
- Max. IR LED 20 metri
- IP66 Waterproof
- DC12V

Modello	OBA MP05		
Sensore/Chipset	1/4" OV9712+Hi3518E		
Risoluzione	1Mega-Pixel 720P		
Pixels effettivi	1280(H)×720(V)		
Mini. Illuminazione	B/W 0.08Lux@F1.2 Color 0.6Lux @F1.2		
Electronic Shutter	PAL:Auto/Manual, 1/3~1/10000s / NTSC: Auto/Manual, 1/4~1/10000s		
Video Frame Rate	PAL:25fps@720P NTSC: 30fps@720P		
Synchronization	Interna		
SNR(Signal Noise	>50dB		
Electronic Shutter	1/50(60)—1/10000sec		
Video Compression	H.264 video encoding, supports dual stream, AVI format; stream 0.1M ~ 8Mpbs; support frame rate 1 to 30 frames/S		
Main stream	1280*720; 704*576;		
Sub Stream	704*576;352*288		
Frame Rate	1-25 fps		
General Function	Reset Software, Watchdog , Auto white balance ,Auto/Manual Gain control,Up to 4 areas Privacy Masking		
Camera Features			
Max. IR Led	IR led: ¢ 5*30pcs IR led, IR distanza : 30m (2pcs Dot LED option)		
Day/Night	Color / Black & White / Auto; IR Cut Filter With Auto Switch		
Noise Reduction	3D		
Lente			
Focal Length	Varifocale 2,8-12mm MP HD lente		
Mount Type	F1.4	Angolo di visione	33°-78°(orizzontale)
Video & Audio			
Video	H.264 / MJPEG,Main stream: 25fps/30fps, Sub stream: D1/CIF.		
Bit Rate:	H.264: 56K ~ 8192Kbps		
Network			
Ethernet	RJ-45 (10/100Base-T),Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP...etc		
Lightning Protection	Power,Net,POE Full Lightning protection,Standard GB/T17626.5 & IEC61000-4-5		
Funzioni:	Supporta WEB configuration, supporta OSD, supporta real-time video transmission, Supporta motion detection linkage e storage; support JPEG		
Onvif	capture; Screen Pop-up Linkage;Support client software remote monitoring(CMS),		
Remote View	Computer: IE6.0 e successivi,Max 10 users		
Smart Phone	Mobile Phone: iPhone, iPad, Android, Android pad		
Auxiliary Interface			
P2P/Cloud	SI, Support QR Code		
WiFi	Si		
Generale			
Power Supply	DC12V±10%; Max 2W		
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)		
Vandal Resistance	IP66 Waterproof		
Dimensioni(W×D×H)	185(L)x65.55(W)x65.55(H)mm		
Peso	450g		