



### Caratteristiche

- 1/3" 4.0 Megapixel AHD low lux
- TV system PAL/NTSC
- Supporta AHD CVBS switch via OSD/UTC
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- High speed, distanza di trasmissione 500m
- Supporta 2D/3D noise reduction,digital wide dynamic
- 2.8-12mm Varifocal HD lente
- IP66 Waterproof, Aluminium
- Power: DC12V

| Modello                  | Oba AHD-F10                                                  |
|--------------------------|--------------------------------------------------------------|
| Video Output             | AHD /CVBS                                                    |
| Camera                   |                                                              |
| Sensore Immagine         | OV4689                                                       |
| DSP                      | NVP2475                                                      |
| Resoluzione              | HD 4.0MP                                                     |
| Pixel Effettivi          | 4.0MP,2592(H)×1520(V)                                        |
| Min.Illuminazione        | 0.1Lux@F1.2                                                  |
| TV System                | PAL/NTSC                                                     |
| Electronic Shutter       | 1/25s~1/50,000s , 1/30s~1/60,000s                            |
| S/N Ratio                | ≥55dB                                                        |
| Scanning System          | Progressive Scan                                             |
| Lente                    |                                                              |
| Focus Length             | 2.8-12mm/F2.0                                                |
| Focus Control            | Varifocal                                                    |
| Auto Focus               | -                                                            |
| Auto Iris Support        | -                                                            |
| Visione Notturna         |                                                              |
| LED Infrarossi           | 42 SMD IR LED                                                |
| IR Distanza              | 40-45 metri                                                  |
| Day/Night                | Colore / Black & White / Auto; IR Cut filtro con Auto Switch |
| IR Status                | Under 10 Lux by CDS,                                         |
| IR Power On              | CDS/Photodiode Auto Control                                  |
|                          | -                                                            |
| Caratteristiche Camera   |                                                              |
| OSD                      | UTP                                                          |
| UTC                      | SI                                                           |
| Menu                     | EN, CN, DE, FRA, IT, ES, PL, RU, PT, NL, TK                  |
| White Balance            | Auto<br>/Manual                                              |
| Gain Control             | Auto                                                         |
| Noise Reduction          | 3D NR                                                        |
| Picture Adjustment       | YES                                                          |
| WDR                      | DWDR                                                         |
| Generale                 |                                                              |
| Case                     | Aluminio ,Vandalproof                                        |
| Supporto                 | SI-AxisBracket                                               |
| Dual Voltage             | NO                                                           |
| IR Cut Filtro            | SI                                                           |
| Heater                   | NO                                                           |
| Temperatura              | -20℃ ~ +50℃ RH95% Max                                        |
| Storage Temperatur       | -30℃ ~ +60℃ RH95% Max                                        |
| Power                    | DC12V±10%, 500mA                                             |
| Distanza di Trasmissione | 500 Metri via 75-3 cavo coaxial                              |
| Dimensioni               | 274.8*90.7*79.2mm                                            |
| Peso                     | 1250g                                                        |